

RADIATORE



IT IMPIEGO

Tube in gomma cord idoneo per passaggio di acqua calda mista a liquidi antigelo.

Normative di riferimento: DIN 73411.

- **TEMPERATURA:** -40°C +120°C

STRUTTURA

- **Sottostrato:** liscio in gomma nera EPDM resistente al calore.
- **Rinforzi:** tessuti sintetici ad alta resistenza.
- **Copertura:** in gomma nera EPDM resistente all'abrasione, al calore e all'invecchiamento.
- **Superficie:** liscia ad impressione tela.
- **Marchatura:** listino in rilievo "H.T. - RADIATORE -40°C +120°C - d.i. - DIN 73411".

EN APPLICATION

Softwall rubber hose suitable for conveying hot water mixed with cooling liquids.

Standards: DIN 73411.

- **TEMPERATURE RANGE:** -40°C +120°C

CONSTRUCTION

- **Tube:** black, smooth, heat resistant EPDM rubber.
- **Reinforcement:** high strength synthetic textile plies.
- **Cover:** black, abrasion, heat and ageing resistant EPDM rubber.
- **Surface:** smooth fabric finished.
- **Branding:** embossed "H.T. - RADIATORE -40°C +120°C - i.d. - DIN 73411".

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESS. SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
18	23/32"	27	1.1/16"	0.28	0.19	4	60	12	180	1/20	3.28/65.5
19	3/4"	28	1.3/32"	0.29	0.20	4	60	12	180	1/20	3.28/65.5
20	25/32"	29	1.5/32"	0.30	0.20	4	60	12	180	1/20	3.28/65.5
22	7/8"	31	1.7/32"	0.33	0.22	4	60	12	180	1/20	3.28/65.5
25	1"	34	1.3/8"	0.42	0.28	4	60	12	180	1/20	3.28/65.5
28	1.3/32"	37	1.15/32"	0.46	0.31	4	60	12	180	1/20	3.28/65.5
30	1.3/16"	39	1.17/32"	0.58	0.39	4	60	12	180	1/20	3.28/65.5
32	1.1/4"	41	1.21/32"	0.62	0.42	4	60	12	180	1/20	3.28/65.5
35	1.3/8"	44	1.23/32"	0.67	0.45	4	60	12	180	1/20	3.28/65.5
38	1.1/2"	48	1.7/8"	0.82	0.55	4	60	12	180	1/20	3.28/65.5
40	1.9/16"	50	1.31/32"	0.86	0.58	4	60	12	180	1/20	3.28/65.5
42	1.21/32"	52	2.1/16"	0.90	0.61	4	60	12	180	1/20	3.28/65.5
45	1.3/4"	55	2.5/32"	1.02	0.69	4	60	12	180	1/20	3.28/65.5
48	1.7/8"	58	2.9/32"	1.07	0.72	4	60	12	180	1/20	3.28/65.5
50	1.31/32"	60	2.3/8"	1.13	0.76	4	60	12	180	1/20	3.28/65.5
55	2.5/32"	65	2.9/16"	1.20	0.80	4	60	12	180	1/20	3.28/65.5
60	2.3/8"	70	2.3/4"	1.28	0.86	4	60	12	180	1/20	3.28/65.5
65	2.9/16"	75	3"	1.51	1.01	4	60	12	180	1/20	3.28/65.5
70	2.3/4"	80	3.5/32"	1.60	1.07	4	60	12	180	1/20	3.28/65.5
76	2.15/16"	86	3.3/8"	1.70	1.14	4	60	12	180	1/20	3.28/65.5
80	3"	90	3.17/32"	1.82	1.22	4	60	12	180	1/20	3.28/65.5
90	3.5/32"	102	4"	2.15	1.44	4	60	12	180	1/20	3.28/65.5
100	3.15/16"	113	4.7/16"	2.30	1.54	4	60	12	180	1/20	3.28/65.5
115	4.5/8"	128	5.1/8"	3.20	2.15	3	45	9	135	20	65.5

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.